

NanoStation loco M2

AirOS™

MAIN

WIRELESS

NETWORK

ADVANCED

SERVICES

SYSTEM

Tools:

Logout

Basic Wireless Settings

Wireless Mode: [?] Access Point

SSID: ubnt ☐ Hide SSID

Country Code: Italy ☒ Obey Regulatory Rules

IEEE 802.11 Mode: B/G/N mixed

Channel Width: [?] 20 MHz

Channel Shifting: [?] Disabled

Frequency, MHz: 2412

Extension Channel: None

Output Power: 12 dBm

Max TX Rate, Mbps: MCS 15 - 130 ☒ Automatic

Wireless Security

Security: none

MAC ACL: ☐ Enabled

Change

© Copyright 2006-2010 Ubiquiti Networks, Inc.



MAIN

WIRELESS

NETWORK

ADVANCED

SERVICES

SYSTEM

Tools:

Logout

AirMax Settings

Enable AirMax: ☐No ACK Mode for PtP: ☐

Advanced Wireless Settings

RTS Threshold: 2346 ☒ OffFragmentation Threshold: 2346 ☒ OffDistance: 0.4 miles (0.6 km)ACK Timeout: 31 ☒ Auto AdjustAggregation: ☒ Enable 32 Frames 50000 BytesMulticast Data: ☒ Allow AllEnable Extra Reporting: ☒Enable Client Isolation: ☐

Advanced Ethernet Settings

Enable Autonegotiation: ☒Link Speed, Mbps: 100Enable Full Duplex: ☒

Signal LED Thresholds

	LED1	LED2	LED3	LED4
Thresholds, dBm:	- 94	- 80	- 73	- 65

Traffic Shaping

Enable Traffic Shaping: ☐

Change

© Copyright 2006-2010 Ubiquiti Networks, Inc.