

CONNECTORS / ADAPTORS



SMA-female

Crimp type available for
RG58, CO100 - P/N 30.SMA003.00
RG174, RG316 - P/N 30.SMA004.00



SMA-male

Crimp type available for
RG58, CO100 - P/N 30.SMA001.00
RG174, RG316 - P/N 30.SMA002.00



SMA-m (Rev Pol)

Crimp type available for
RG58, CO100 - P/N 30.SMA005.00
RG174, RG316 - P/N 30.SMA006.00



TNC-male

Crimp type available for
RG58, CO100 - P/N 30.TNC001.00



N-male

Crimp type available for
RG58, CO100 - P/N 30.N001.00



N-female

Crimp type available for
RG58, CO100 - P/N 30.N002.00



FME-male

Crimp type available for
RG58, CO100 - P/N 30.FME001.00
RG174, RG316 - P/N 30.FME005.00



FME-female

Crimp type available for
RG58, CO100 - P/N 30.FME002.00
RG174, RG316 - P/N 30.FME003.00
Low Loss - P/N 30.FME004.00



BNC-male

Crimp type available for
RG58, CO100 - P/N 30.BNC001.00



FME-m/Mini UHF-m

Adaptor - P/N 30.AD004.00



FME-m/BNC-m

Adaptor - P/N 30.AD005.00



FME-m/N-m

Adaptor - P/N 30.AD006.00

COAXIAL CABLES - Data table

	RG 58 C/U	CO 100	RG 174	RG 316/U
Impedance	50 Ω	50 Ω	50 Ω	50 Ω
External diameter	4.95 mm	4.95 mm	2.8 mm	2.5 mm
Colour	Black	White	Black	Brown
Attenuation dB/100m				
@ 1.8 GHz	70	45	133	126
@ 2.0 GHz	76	48	141	134
@ 2.2 GHz	78	50	150	141
@ 2.4 GHz	86	53	159	149
@ 2.5 GHz	87	54	162	152

GOT IT!
Feb 2004

