

Versione con Kernel 1.37

**Administrator:**

- [Authentication](#)
- [System IP](#)
- [System Status](#)
- [Load default setting](#)

**Functions:**

- [TCP Mode](#)
- [UDP Mode](#)
- [UART](#)
- [Reset Device](#)

## System Status

Kernel Version	V1.37n 2008/12/04
MAC Address	00:11:22:4E:0A:39
Nickname	<input type="text" value="ATC-1000"/> <input type="button" value="Update"/>

Versione con Kernel 1.43

**[Administrator Setting](#)**

- [TCP Mode](#)
- [UDP Mode](#)
- [UART](#)
- [Reset Device](#)

## Administrator Setting

Kernel Version	V1.43 2010/01/21
MAC Address	00:11:22:68:24:3C
Nickname	<input type="text" value="NetUART"/>
IP Setting	
IP Address	<input type="text" value="192"/> . <input type="text" value="168"/> . <input type="text" value="0"/> . <input type="text" value="95"/>
Subnet Mask	<input type="text" value="255"/> . <input type="text" value="255"/> . <input type="text" value="255"/> . <input type="text" value="0"/>
Gateway	<input type="text" value="192"/> . <input type="text" value="168"/> . <input type="text" value="2"/> . <input type="text" value="1"/>
IP Configure	<input checked="" type="radio"/> Static <input type="radio"/> DHCP
Password Setting	
Username	<input type="text" value="admin"/> max:15
Password	<input type="password" value="••••••"/> max:15
Confirm	<input type="password" value="••••••"/>
<input type="button" value="Update"/>	
Load Default Setting to EEPROM	<input type="button" value="Load"/>

Note:

Nickname only can use "0-9","a-z","A-Z","\_","-"