

Figura 1: ATC-3000 Hotlist Settings:

192.168.1.250

Home  
Basic Setting  
Network  
Server  
Serial Tunnel 0  
Hostlist  
Channel 0  
Serial Settings  
Connection  
Password Setting  
Load Defaults  
Apply/Restart  
Log Out

### Hostlist Settings

Channel 0

**Retry Settings**  
 Retry Counter: 2    Retry Timeout: 1

**Host Information**

No.	Host Address	Port	No.	Host Address	Port
1	192.168.1.10	10002	2	0.0.0.0	0
3	0.0.0.0	0	4	0.0.0.0	0
5	0.0.0.0	0	6	0.0.0.0	0
7	0.0.0.0	0	8	0.0.0.0	0
9	0.0.0.0	0	10	0.0.0.0	0
11	0.0.0.0	0	12	0.0.0.0	0

Backup Link:  Enable  Disable

OK

Figura 2: ATC-3000 Serial Settings

192.168.1.250

Home  
Basic Setting  
Network  
Server  
Serial Tunnel 0  
Hostlist  
Channel 0  
Serial Settings  
Connection  
Password Setting  
Load Defaults  
Apply/Restart  
Log Out

### Serial Settings

Channel 0

**Port Settings**  
 Protocol: RS232    FIFO: 8    Flow Control: None  
 Baud Rate: 1200    Data Bits: 8    Parity: NONE    Stop bits: 1

**Pack Control**  
 Enable Packing  
 Idle Gap Time: 10 msec  
 Match 2 Byte Sequence:  Yes  No    Send Frame Only:  Yes  No  
 Match Byte: 0x    0x (Hex)    Send Trailing Bytes:  None  One  Two

**Flush Mode**

**Flush Input Buffer**  
 With Active Connect:  Yes  No  
 With Passive Connect:  Yes  No  
 At Time of Disconnect:  Yes  No

**Flush Output Buffer**  
 With Active Connect:  Yes  No  
 With Passive Connect:  Yes  No  
 At Time of Disconnect:  Yes  No

OK

Figura 3: ATC-3000 Connection Settings

192.168.1.250

Home  
Basic Setting  
Network  
Server  
Serial Tunnel 0  
Hostlist  
Channel 0  
Serial Settings  
Connection  
Password Setting  
Load Defaults  
Apply/Restart  
Log Out

### Connection Settings

Channel 0

**Connection Protocol:** TCP

**Passive Connection:** Acceptation Incoming: Yes

**Active Connection:** Active Connect: None  
 Start Character: 0x00 (in Hex)

**Connection Configuration:**  
 Local Port: 10001    Remote Port: 10001  
 Remote Host: IP REMOTO\*\*\*    DNS Query Period: 1800 (Secs)  
 Connect Response: ACT    Use Hostlist:  Yes  No

**Disconnect Mode**  
 On Mdm\_Ctrl\_In Drop:  Yes  No    Hard Disconnect:  Yes  No  
 Check EOT(Ctr-D):  Yes  No    Inactivity Timeout: 4 : 15 (mins:secs)